

Technical Data **wood Parquet** "Manor House varnished Collection"

Specifications	
construction	multilayer parquet, 1-strip plank WICANDERS ® „Loc&Fold system“, bevel 2 sides
according standard	DIN EN 13489 / 2023-09
species	Oak
hardness (Brinell)	approx. 38 N/mm ²
moisture content	7 % (± 2 %)
heat transmission resistance	approx. 0,105 m ² K/W suitable for floor heating systems max. 26° C
fire resistance class	Dfl - s1 (normally inflammable)
emission of formaldehyde	class E1 (< 0,1 ppm)
dimensions	
length	1900 mm
width	190 mm
thickness	14 mm
wear layer	3,0 mm, several renovations of the wear layer are possible
quantity pack	8 layers / pack = 2,888 m ² occasionally, short lengths are possible
quantity pallet	40 pack / pallet = 115,520 m ²
products	
82000272 / RW04441B, "Carlisle"	Oak Nature 1-strip, supermat varnished, brushed, visual unfinished, bevel 2 sides
82000280 / RW04446A, "Keppel"	Oak Country 1-strip, supermat varnished, brushed, visual unfinished, bevel 2 sides
82000286 / RW04451A, "Jersey"	Oak Nature 1-strip, supermat varnished, brushed, bevel 2 sides
82000287 / RW04452, "Stanley"	Oak Rustic 1-strip, supermat varnished, brushed, bevel 2 sides
82000288 / RW04453, "Fane"	Oak Rustic 1-strip, supermat varnished, brushed, grey, bevel 2 sides