

## Technical Data **wood Parquet** "Basic Collection"

Specifications	
construction	multilayer parquet, 1-strip plank <b>WICANDERS</b> ® „Loc&Fold-System“, 4 side bevel, 2 side bevel <sup>(1)</sup>
according standard	DIN EN 13489   2017-12
species	Oak
hardness (Brinell)	approx. 38 N/mm <sup>2</sup>
moisture content	7 % (± 2 %)
heat transmission resistance	approx. 0,105 m <sup>2</sup> K/W suitable for floor heating systems max. 26° C
fire resistance class	Dfl - s1 (normally inflammable)
emission of formaldehyde	class E1 (< 0,1 ppm)

dimensions	
length	1900 / 2200 <sup>(2)</sup> mm
width	190 / 260 <sup>(2)</sup> mm
thickness	14 mm
wear layer	2,5 mm, several renovations of the wear layer are possible
quantity pack	8 layers / pack = 2,888 m <sup>2</sup> 6 layers / pack = 3,432 m <sup>2</sup> <sup>(2)</sup> occasionally, short lengths are possible
quantity pallet	40 pack / pallet = 115,520 m <sup>2</sup> 28 pack / pallet = 96,096 m <sup>2</sup> <sup>(2)</sup>

products	
820001757 / RW04357B, "Lisbon"	Oak Country 1-strip, brushed, white oiled, 4 sides bevelled
82000178 / RW04357C, "Vienna"	Oak Country 1-strip, white oiled, 4 sides bevelled
82000256 / RW04401A, "Basel"	Oak Country 1-strip, brushed, smoked, oiled, 4 sides bevelled
82000259 / RW04402B, "Riga"	Oak Country 1-strip, brushed, oiled, 4 sides bevelled
82000260 / RW04402C, "Marseille"	Oak Country 1-strip, oiled, 4 sides bevelled
82000323 <sup>(1)</sup> / RW04472B <sup>(1)</sup> , "Krakow"	Oak Country 1-strip, brushed, supermat varnished, bevelled 2 sides
82000268 <sup>(1)</sup> / RW04419A <sup>(1)</sup> , "Amsterdam"	Oak Nature 1-strip, oiled, bevelled 2 sides
82000310 <sup>(2)</sup> / RW0446 <sup>(2)</sup> , "Rotterdam"	Oak Country 1-strip, brushed, oiled, 4 sides bevelled
82000311 <sup>(2)</sup> / RW04468 <sup>(2)</sup> , "Paris"	Oak Country 1-strip, brushed, white oiled, 4 sides bevelled