

## Technical Data **wood Parquet "Jewel Collection"**

Specifications	
construction	multilayer parquet, 1-strip plank <b>WICANDERS®</b> „Loc&Fold system“, bevel 4 sides / bevel 2 sides <sup>(1)</sup>
according standard	DIN EN 13489   2017-12
species	Oak
hardness (Brinell)	approx. 38 N/mm <sup>2</sup>
moisture content	7 % (± 2 %)
heat transmission resistance	approx. 0,110 m <sup>2</sup> K/W suitable for floor heating systems max. 26° C
fire resistance class	Dfl - s1 (normally inflammable)
emission of formaldehyde	class E1 (< 0,1 ppm)
dimensions	
length	2200 mm
width	220 mm
thickness	15 mm
wear layer	4,0 mm, several renovations of the wear layer are possible
quantity pack	6 layers / pack = 2,904 m <sup>2</sup> occasionally, short lengths are possible
quantity pallet	44 pack / pallet = 127,776 m <sup>2</sup>
products	
82000237 <sup>(1)</sup> / RW04391 <sup>(1)</sup> , "Diamond"	Oak Nature 1-strip, oiled, bevel 2 sides
82000239 <sup>(1)</sup> / RW04392 <sup>(1)</sup> , "Topas"	Oak Nature 1-strip, half white oiled, bevel 2 sides
82000241 / RW04393, "Amethyst"	Oak Rustic 1-strip, brushed, handscraped, stained, embossed knots, oiled, bevel 4 sides
82000242 / RW04394, "Carnelian"	Oak Rustic 1-strip, brushed, handscraped, embossed knots, smoked, whitewashed, white oiled, bevel 4 sides
82000243 / RW04395, "Ruby"	Oak Rustic 1-strip, deep brushed, sawn marks, large cracks, smoked, oiled, bevel 4 sides
82000245 / RW04396, "Beryl"	Oak Rustic 1-strip, deep brushed, sawn marks, large cracks, smoked, whitewashed, white oiled, bevel 4 sides
82000247 / RW04397, "Emerald"	Oak Rustic 1-strip, light handscraped, oiled, bevel 4 sides