

Technical Data **wood Parquet** "Kentucky Collection Antique"

Specifications	
construction	multilayer parquet, 2-strip plank (1-strip plank) ⁽¹⁾ WICANDERS ® „Loc&Fold-System“, bevel 4 sides
according standard	DIN EN 13489 2017-12
species	Oak
hardness (Brinell)	approx. 38 N/mm ²
moisture content	7 % (± 2 %)
heat transmission resistance	approx. 0,110 m ² K/W suitable for floor heating systems max. 29° C
fire resistance class	Dfl - s1 (normally inflammable)
emission of formaldehyde	class E1 (< 0,1 ppm)
dimensions	
length	1830 mm / 1900 mm ⁽²⁾
width	189 mm / 190 mm ⁽²⁾
thickness	15 mm
wear layer	4,0 mm, several renovations of the wear layer are possible
quantity pack	8 layers / pack = 2,767 m ² 8 layers / pack = 2,888 m ²⁽²⁾ occasionally, short lengths are possible
quantity pallet	40 pack / pallet = 110,680 m ² 40 pack / pallet = 115,520 m ²⁽²⁾
products	
82000180 ⁽¹⁾⁽²⁾ / RW04359A ⁽¹⁾⁽²⁾ , "New Hampshire"	Oak Rustic 1-strip, antique, brushed, deep smoked, aged visual, oiled, bevel 4 sides
82000182 / RW04360A, "Vermont"	Oak Rustic 2-strip, antique, brushed, deep smoked, aged visual, oiled, bevel 4 sides
82000184 / RW04361A, "Rhode Island"	Oak Rustic 2-strip, antique, brushed, deep smoked, aged visual, white oiled, bevel 4 sides