

Technical Data **wood Parquet "Kentucky Rustic Collection"**

Specifications	
construction	multilayer parquet, 1-strip plank WICANDERS® „Loc&Fold-System“, bevel 4 sides
according standard	DIN EN 13489 2017-12
species	Oak
hardness (Brinell)	approx. 38 N/mm ²
moisture content	7 % (± 2 %)
heat transmission resistance	approx. 0,110 m ² K/W suitable for floor heating systems max. 26° C
fire resistance class	Dfl - s1 (normally inflammable)
emission of formaldehyde	class E1 (< 0,1 ppm)
dimensions	
length	1900 mm / 1830 mm ⁽³⁾
width	190 mm / 189 mm ⁽³⁾
thickness	15 mm
wear layer	4,0 mm
quantity pack	8 layers / pack = 2,888 m ² 8 layers / pack = 2,767 m ²⁽³⁾ occasionally, short lengths are possible
quantity pallet	40 pack / pallet = 115,52 m ² 40 pack / pallet = 110,68 m ²⁽³⁾
products	
82000163 / RW04319C, "Grand Canyon"	Oak Rustic 1-strip, antique, deep brushed, smoked, sawn marks, large cracks, volcanic stain, white washed, oiled, bevel 4 sides
82000165 / RW04320C, "Denver"	Oak Rustic 1-strip, antique, deep brushed, smoked, sawn marks, large cracks, oiled, bevel 4 sides
82000168 / RW04321C, "Santa Fe"	Oak Rustic 1-strip, antique, deep brushed, deep smoked, sawn marks, large cracks, white washed, oiled, bevel 4 sides
82000170 / RW04322C, "Colorado City"	Oak Rustic 1-strip, antique, deep brushed, smoked, sawn marks, large cracks, white washed, oiled, bevel 4 sides