

Technical Data **wood Parquet** "Kentucky Standard Collection"

Specifications	
construction	multilayer parquet, 1-strip plank WICANDERS ® „Loc&Fold-System“, bevel 4 sides (bevel 2 sides) ⁽²⁾
according standard	DIN EN 13489 2017-12
species	Oak
hardness (Brinell)	approx. 38 N/mm ²
moisture content	7 % (± 2 %)
heat transmission resistance	approx. 0,110 m ² K/W suitable for floor heating systems max. 26° C
fire resistance class	Dfl - s1 (normally inflammable)
emission of formaldehyde	class E1 (< 0,1 ppm)
dimensions	
length	1900 mm / 1830 mm ⁽³⁾
width	190 mm / 189 mm ⁽³⁾
thickness	15 mm
wear layer	4,0 mm
quantity pack	8 layers / pack = 2,888 m ² 8 layers / pack = 2,767 m ²⁽³⁾ occasionally, short lengths are possible
quantity pallet	40 pack / pallet = 115,52 m ² 40 pack / pallet = 110,68 m ²⁽³⁾
products	
82000118 / RW04242C, "Oklahoma"	Oak Rustic 1-strip, smoked, oiled, bevel 4 sides
82000121 / RW04243C, "Dallas"	Oak Rustic 1-strip, handscraped, oiled, bevel 4 sides
82000125 / RW04244C, "Houston"	Oak Rustic 1-strip, handscraped, white oiled, bevel 4 sides
82000136 ⁽²⁾ / RW04247D ⁽²⁾ , "New Orleans"	Oak Nature 1-strip, brushed, white washed, oiled, bevel 2 sides
82000131 / RW04246C, "Atlanta"	Oak Rustic 1-strip, smoked, brushed, white washed, oiled, bevel 4 sides