

Technical Data **wood Parquet** "Victoria Collection"

Specifications	
construction	multilayer parquet, 1-strip plank WICANDERS ® „Loc&Fold-System“, bevel 4 sides
according standard	DIN EN 13489 2017-12
species	Oak
hardness (Brinell)	approx. 38 N/mm ²
moisture content	7 % (± 2 %)
heat transmission resistance	approx. 0,110 m ² K/W suitable for floor heating systems max. 26° C
fire resistance class	Dfl - s1 (normally inflammable)
emission of formaldehyde	class E1 (< 0,1 ppm)
dimensions	
length	1900 mm
width	190 mm
thickness	15 mm
wear layer	4,0 mm, several renovations of the wear layer are possible
quantity pack	8 layers / pack = 2,888 m ² occasionally, short lengths are possible
quantity pallet	40 pack / pallet = 115,52 m ²
products	
82000138 / RW04253C, "Sand"	Oak Rustic 1-strip, rustic, knotty, brushed, handscraped, oiled, bevel 4 sides
82000147 / RW04256C, "Grafitte"	Oak Rustic 1-strip, rustic, knotty, brushed, handscraped, smoked, black washed, oiled, bevel 4 sides
82000150 / RW04258C, "Copper"	Oak Rustic 1-strip, rustic, knotty, brushed, handscraped, smoked, brown washed, oiled, bevel 4 sides
82000140 / RW04254C, "Ivory"	Oak Rustic 1-strip, rustic, knotty, brushed, handscraped, smoked, white oiled, bevel 4 sides
82000143 / RW04255C, "Steel"	Oak Rustic 1-strip, rustic, knotty, brushed, handscraped, smoked, white washed, white oiled, bevel 4 sides
82000284 / RW04450A, "Pebble"	Oak Rustic 1-strip, rustic, knotty, brushed, handscraped, deep smoked, white washed, white oiled, bevel 4 sides